

1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO TF DSG

VAICO No.:

V60-0118, V60-0224, V60-0225, V60-0226

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- Excellent wear protection
- Stable friction coefficient characteristic at both high and low temperatures
- Unrivalled viscosity-temperature behaviour
- Outstanding oxidation and ageing stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Universal Dual-clutch transmission
- Do not mix with other transmission fluids.
- Not suitable for use in stepped automatic transmissions or continuously variable transmissions (CVT).
- Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Recommendations*:

VW/Audi TL 521 82

BMW DCTF-1/FFL-4/MTF-5

MB 236.21

PSA 9734.S2

Ford WSS-M2C 936-A

Chrysler 68044345EA

Mitsubishi Dia Queen SSTF-I (MZ320065)

Volvo 1161838/1161839

4.2. Parts number*:

VW G 052 182 (DQ 250/DQ 500)

VW G 052 529 (DL 501)

TYPICAL VALUES	METHOD	UNIT	VAICO TF DSG
Density at 15°C	DIN 51 757	g/cm ³	0,855
Viscosity at 40°C	DIN ISO 3104	mm ² /s	35
Viscosity at 100°C	DIN ISO 3104	mm ² /s	7,0
Viscosity index (VI)	DIN ISO 2909	-	170
COC flash point	DIN ISO 2592	°C	224
Pour point	DIN ISO 3016	°C	- 50

* conforms to OEM specifications

The above values may vary within commercially accepted tolerances